

Get advice.
0860 103 627

VERSATILITY
Get it.

**Head Office
Cape Town** 10th Floor, South African Reserve
Bank Building, Cnr Hout Street and
St George's Mall, Cape Town, 8001
Tel: +27 21 480 3140
Fax: +27 21 424 7710

Atlantis John van Niekerk Street, Atlantis,
7349
PO Box 7024, Roggebaai, 8012
Tel: +27 21 577 1490
Fax: +27 21 577 1791

KwaZuluNatal 41 Suffert Street, Pinetown, 3610
PO Box 7024, Roggebaai, New
Germany 3620
Tel: +27 31 717 5871
Fax: +27 31 701 2265

Gauteng 69 Pomona Road, Pomona,
Kempton Park, 1619
PO Box 5654, Kempton Park, 1620
Tel: +27 11 979 1192
Fax: +27 11 979 1195

www.isotherm.co.za

www.brits.co.za



Installation guide for
hollow wall structures.


ISOTHERM
Thermal Insulation

Manufactured by:

brits
nonwoven


SASO
SOUTH AFRICAN
STANDARDIZATION
ORGANIZATION


AGREMENT
SOUTH AFRICA
innovative construction product assessments


ISOTHERM
Thermal Insulation

Get results.

Get comfort

ISOTHERM keeps you and your family warm in winter and cool in summer.

Get safety

ISOTHERM is made from polyester and is 100% people – friendly. It is safe and easy to install; no gloves or breathing apparatus required.

Get quality

ISOTHERM is manufactured by Brits Nonwoven and is an Agrément certified product. **ISOTHERM** is economical and the best thermal insulation product to use in terms of guaranteed quality.

Get comfort, quality and safety with ISOTHERM THERMAL INSULATION.

Get green

Made from recycled PET bottles, **ISOTHERM** helps to fight unemployment and sustain the ecology and economy of the country.

Depending on the thickness of **ISOTHERM** installed and the climatic zone, **ISOTHERM's** performance is as follows:

In summer

You get maximum temperature reduction of up to 7°C when **ISOTHERM** insulated ceilings are correctly installed.

In winter

You get a reduced heating energy requirement of between 40% and 70% in a standard house.

Get the facts and benefits

Non-toxic

No chemical additives, no odour or emissions of volatile organic compounds.

Fire performance

ISOTHERM complies with SANS 10400 The Application of the National Building Regulations, as an insulation material.

Tested in accordance with: SANS 428 : Fire Performance Classification B/B 1/2.

ASTM – E 84 : Spread of flame: nil.

BS 5803 part 4 : Does not smoulder.

Test reports available on request.

ISOTHERM may be used as specified for all types of buildings

Maintenance-free

ISOTHERM is resistant to condensation and associated fungi and bacteria. **ISOTHERM** retains loft and does not degrade over time.

Eco-friendly

ISOTHERM is made using polymer from recycled PET bottles and is completely recyclable.

Energy-saving

ISOTHERM saves energy.

In less than 3 years **ISOTHERM** can pay for itself by savings on electricity usage.

subject to the provisos listed in Part T of Section 3 of SANS 10400.*

THICKNESS	DENSITY	REDUCTION IN HEAT FLOW (Downwards)	THERMAL RESISTANCE 'R' VALUE	NOISE REDUCTION COEFFICIENT	AVAILABLE SIZES LENGTH	AVAILABLE SIZES WIDTH
40mm	10kg/m ³	69%	0.88	N/A	10m	750 / 1200mm
50mm	10kg/m ³	72%	1.10	0.6	10m	750 / 1200mm
75mm	10kg/m ³	78%	1.65	0.75	8m	750 / 1200mm
100mm	10kg/m ³	83%	2.20 <small>(as tested by SABS)</small>	0.75	6m <small>(as tested by SABS)</small>	750 / 1200mm

*SANS 10400 – 1990. The application of the National Building Regulations.

Exterior Timber Frame Walling



ISOTHERM is safe and easy to install and will not sag in hollow wall frame structures.

ISOTHERM will not support the spread of flame



Get prepared

ISOTHERM is supplied in roll form; allowing you to cut to your customised size and shape. This is easily done by tearing or cutting with a pair of industrial scissors or shears.

Cut the **ISOTHERM** to size or slightly bigger than the frame size depending on the thickness of product used.

A minimum of 50mm is recommended. Variable widths are available.



Get it done

Position **ISOTHERM** correctly. Position closely to the cladding material and ensure a snug fit.

Ensure continuous insulation. Carefully butt the ends of the rolls or lap to ensure maximum effectiveness.

Ensure that the **ISOTHERM** is positioned behind cables, conduits and plug points, leaving them exposed.

Do not waste off-cuts. Use them wisely by filling in gaps, crevices and corners.

